

IN THE CLAIMS

1 (Currently Amended). A method comprising:
determining a color gamut that a substantial portion of the sub-pixels of an expressed color of an organic light emitting device display are able to achieve; ~~and~~
adjusting the drive current to the sub-pixels to achieve that color gamut; and
maintaining said gamut substantially constant over the lifetime of said display.

2 (Original). The method of claim 1 including determining a color gamut that all of the subpixels of an expressed color gamut can achieve and adjusting the device current to achieve that color gamut.

Claim 3 (Canceled).

4 (Original). The method of claim 1 including maintaining said gamut substantially constant by mixing a first or second subpixel color with an expressed color pixel to adjust the color of the expressed color pixel.

5 (Original). The method of claim 1 including mixing colors of a tricolor color space to achieve said color gamut.

6 (Currently Amended). An article comprising a medium storing instructions that enable a processor-based system to:

determine a color gamut that a substantial portion of the sub-pixels of an expressed color of an organic light emitting device display are able to achieve; ~~and~~
adjust the drive current to the sub-pixels to achieve that color gamut; and
maintain said gamut substantially constant over the lifetime of said display.

7 (Original). The article of claim 6 further storing instructions that enable the processor-based system to determine a color gamut that all of the sub-pixels of an expressed color gamut can achieve and adjust the drive current to achieve that color gamut.

Claim 8 (Canceled).

9 (Original). The article of claim 6 further storing instructions that enable the processor-based system to maintain said gamut substantially constant by mixing a first or second sub-pixel color with an expressed color pixel to adjust the color of the expressed color pixel.

10 (Original). The article of claim 6 further storing instructions that enable the processor-based system to mix colors of a tri-color space to achieve said color gamut.

11 (Currently Amended). An electrical system for an organic light emitting device display comprising:

a drive circuit to drive the pixels of said display;

a processor coupled to said drive circuit; and

a storage coupled to said processor, said storage storing instructions that enable the processor to determine a color gamut that a substantial portion of the sub-pixel of an expressed color gamut of an organic light emitting device display are able to achieve, ~~and~~ adjust the drive current to the sub-pixels to achieve that color gamut, and maintain said color triangles substantially constant over the lifetime of the display.

12 (Original). The system of claim 11 wherein said storage stores instructions that enable the system to determine a color gamut that all of the sub-pixels of an expressed color gamut can achieve and adjust the drive current to achieve that color gamut.

Claim 13 (Canceled).

14 (Original). The system of claim 11 wherein said storage stores instructions that enable the system to maintain the gamut substantially constant by mixing a first or second sub-pixel color with an expressed color pixel to adjust the color of the expressed color pixel.

15 (Original). The system of claim 10 wherein said storage stores instructions that enable the system to mix colors of a tri-color color space to achieve said color gamut.

16 (Currently Amended). A display comprising:
a plurality of organic light emitting sub-pixels of at least three colors;
a drive circuit for driving said sub-pixels to emit light; and
a controller to control said drive current to determine a color gamut that a
substantial portion of the sub-pixels of an expressed color gamut of said display are able to
achieve, ~~and~~ adjust the drive current to the sub-pixels to achieve that color gamut, and maintain
said color triangles substantially constant over the lifetime of the display.

17 (Original). The display of claim 16 wherein said sub-pixels include conjugated
polymers.

18 (Original). The display of claim 16 wherein said sub-pixels include a film including
small molecules.

19 (Original). The display of claim 16 wherein said display includes sub-pixels in the
form of a stacked layer.

20 (Original). The display of claim 16 including a substrate wherein said sub-pixels are
distributed side-by-side across said substrate.

21 (Original). The display of claim 16 wherein said controller determines a color gamut
that all of the sub-pixels of an expressed color gamut can achieve and adjusts the drive current to
achieve that color gamut.